

HINO

3000 Series

Tipper Range

Standard and Wide Cab Models



ADR 80/03 Model 300 Series Tipper Range

* Illustration may contain items not standard to the model

KEY FEATURES

- Factory Tipper Bodies
- Cruise Control
- Dual SRS Airbags
- Ventilated Disc Brakes Front and Rear
- Anti-lock Brake System (ABS)
- Vehicle Stability Control (VSC)
- Traction Control (TC)
- Manual & Automatic Transmission Variants
- Easy Start (Manual Model Only)
- ADR 80/03 Emission using Euro 5
- Also meets EEV emission levels
- Driver Suspension seat (Wide Cab only)
- ECE R-29 Cab Strength Certified (Wide Cab only)

KEY SPECIFICATIONS

GVM Range.	4495 to 8500kg
GCM Range.	7300 to 12000kg
Power	110 kW (Auto & STD Cab)
	121 kW (Wide Man)
Torque	420 Nm (Auto & STD Cab)
	464 Nm (Wide Man)
Transmissions	6 Speed Auto . . . (STD & Wide Cab)
	5 Speed Manual . . . (STD Cab)
	6 Speed Manual . . . (Wide Cab)
Tipper Volume	1.9m ³ , 2.1m ³ , 3.0m ³
Tipper Length.	3.0m, 3.1m, 3.6m



Tipper Range

Engine & Driveline Specifications

ENGINE

Model	N04CUS	N04CUT
	Auto & STD Cab	Wide Cab Manual
Max output ISO Net @ 2500 rpm	110 kW (150 HP)	121 kW (165 HP)
Max Output ISO Net @ 1400rpm	420 Nm	464 Nm
Max Engine Speed	3100 rpm	
Type	Diesel 4 cycle 4 cylinder in line overhead valve, water cooled	
Combustion System	Direct injection type	
Bore & Stroke	104 mm x 118 mm	
Piston displacement	4.009 Lts	
Fuel Injection	Electronic control, common rail type	
Air Intake system	Turbo, intercooled stack type intake	
Air Cleaner	Paper Element	
Fan Clutch	Equipped	
Exhaust	Catalytic convertor with Diesel Particulate Active reduction System (DPR)	
Exhaust Outlet	Horizontal	
Emission Control System	EGR & DPR meeting ADR 80/03 using Euro 5. Also meeting EEV emission levels	

CLUTCH (Manual models only)

Clutch type	Dry single plate, diaphragm type with damper springs
Facing outside diameter	325mm
Facing lining area	423cm ² x 2
Control	Hydraulic with vacuum booster

TRANSMISSION

Auto	A860E Full automatic 6 speed with double overdrive
Manual (Wide Cab)	MZZ6F 6 speed sychromesh with single overdrive
Manual (STD Cab)	M550 5 speed manual with single overdrive

BRAKES

Service brakes	Hydraulic system with ventilated disc brakes front and rear
Control	Vacuum servo with hydraulic assist & dual circuits
Anti Lock Braking System (ABS)	Equipped
Vehicle Stability Control (VSC)	Equipped
Traction Control (TRC)	Equipped
Easy Start System (ES)	Equipped (manual models only)
Exhaust Brake	Electro Vacuum actuator with valve in the exhaust pipe
Park Brake	Rear of Transmission

PERFORMANCE & GEAR RATIOS

For performance data, see the table on the back page.

A860E Automatic transmission (STD & Wide Cab)

1st	3.743	5th	0.773
2nd	2.003	6th	0.634
3rd	1.343	Rev.	3.697
4th	1.000		

MZZ6F Manual transmission (Wide Cab)

1st	6.369	5th	1.000
2nd	3.767	6th	0.782
3rd	1.966	Rev.	6.369
4th	1.355		

M550 Manual transmission (Std Cab)

1st	4.981	4th	1.000
2nd	2.911	5th	0.738
3rd	1.556	Rev.	4.625

ELECTRICAL

Type	24 volt, negative earth
Batteries	12V x 2, series connected
Alternator type	Built-in rectifier and voltage regulator
Capacity	24V – 80AMP
Starter capacity	24V, 4.5kW

CHASSIS FRAME

Type	Ladder-shaped channel section side rails
Chassis width at rear	750mm (Wide Cab) 700mm (STD Cab)
Tensile strength	540N/mm ² (Wide Cab) 440N/mm ² (STD Cab)
Towing hooks	Equipped at front and rear

STEERING

Wide Cab	Recirculating Ball with integral Power steering
STD Cab	Rack & pinion with Power Steering

CAB EXTERIOR

Type	Forward control, all steel welded construction, torsion-bar tilt mechanism, fully trimmed
Windscreen wipers	Electric, dual wipers, intermittent and 2-speed
Outside rear mirrors	Remote control and heated & two convex spotters
Radiator grille	Painted same colour as cabin
Lamps	Halogen headlamps and fog lamps



Tipper Range


Cab Equipment, Power Charts & Body Details



CAB INTERIOR

Steering	Telescopic tilt column with integral power steering
Windscreen glass	Laminated glass
Seating capacity	Three
Driver's seat (Wide Cab)	4-way adjustable, urethane pads, high-back, lumbar support with suspension base
(STD Cab)	2-way adjustable, with urethane foam pads
Assistant's seat	Fixed bench, urethane foam pads, high-back
Seat cover	Fabric cover
Seat belts	
Driver's seat	3-point type with ELR and pre-tensioner
Assistant's seat	3-point tyre with ELR and pre-tensioner
Centre passenger's seat	2-point type
Sun visors	For driver and passenger
Ventilator	Forced type by electric blower
Inside rear mirror	One, flat type
Cigarette lighter (24 volt)	Equipped
Audio	DAB+ AM/FM radio with CD & DVD player & Bluetooth
Heater and defroster	Equipped
Air conditioner	Equipped
Remote door locking	Equipped
Immobiliser	Equipped
Power windows	Equipped
SRS airbags	Equipped for driver and assistant
Drivers foot rest	Equipped (Auto models only)
Seat back console	Equipped (Wide Cab only)
Overhead consoles	For driver and assistant
Cup holder	Equipped
Cruise control	Equipped

COMBINED POWER & TORQUE CHART (ISO Net) N04C UT & N04C US



TIPPER BODY DETAILS

Model	616 IFS Auto & Manual	616 Auto & 617 Manual	716 Auto & 717 Manual	917 Manual
Capacity	1.9m ³	2.1m ³	3.0m ³	
Body Length	3.0m	3.1m	3.6m	
Body Width	1750mm	1900mm	2000mm	
Body Side Height	370mm		430mm	
Tipping Angle (deg)	60		55	
Deck Plate Thickness	3.2mm			4.5mm
Front Plate Thickness	3.2mm		2.3mm	3.2mm
Side & Tailgate Thickness	2.3mm			3.2mm
Hydraulic Cylinder Bore & Stroke	100 x 350mm		100 x 480mm	
PTO	On transmission			
Hydraulic Pump	Type	Gear type		
	Model	VC02-04 (Auto) VC02-03 (Man)	VC02-06	VC03-15
PTO & Tip Control	Lever in cab			
Tailgate	Hinged from top			

INSTRUMENTS

1. Meters and gauges

- km-kg system
- Engine tachometer
- Speedometer

2. Warning, pilot lamps and buzzers

- Turning signal & hazard indicator lamp
- Exhaust brake indicator lamp
- Engine oil pressure warning lamp
- Battery charge warning lamp
- High beam indicator lamp
- Parking brake indicator lamp
- Engine malfunction indicator lamp
- Fuel level warning lamp
- Fuel filter water accumulating level warning lamp
- Brake fluid level warning lamp
- Back-up warning buzzer
- Cab-tilt warning lamp
- ABS system failure warning lamp
- SRS airbag system failure warning lamp
- Easy Start indicator lamp*
- Cruise Control

3. Switches

- Lighting switch
- Wiper and washer switch
- Exhaust brake switch
- Easy Start switch*
- Easy Start release timing adjuster switch*
- Cruise Control
- Traction Control OFF

4. Multi Information Display

- Fuel gauge
- Coolant temperature gauge
- DPR accumulation gauge
- Odometer
- 2 trip meters
- Fuel consumption
- Current
- Average

5. Others

- One-key starting-stopping
- Horn button
- Remote door locking

* Easy start components are for Manual models only



Tipper Range Dimensions

300 Series

DIMENSIONS - mm / Capacities

Models	616 IFS Tipper	616 Auto IFS Tipper	616 Auto Tipper	617 Tipper	716 Auto Tipper	717 Tipper	917 Tipper
Product Code	XZU 605R-HKMMSQ3 D	XZU 605R-HKTMSQ3 D	XZU700R-HKTMSQ3 D	XZU700R-HKFMTQ3 D	XZU710R-HKTQSQ3 D	XZU710R-HKFQTQ3 D	XZU710R-HKFTTQ3 D
Chassis Max Section Depth x Flange x thickness	180 x 65 x 6.0	177.8 x 60 x 4.9	190.8 x 65 x 4.9	190.8 x 65 x 4.9	192.8 x 65 x 5.9	192.8 x 65 x 5.9	192.8 x 65 x 5.9
Turning Circle	Kerb to Kerb	9600	9600	9800	9800	11600	12400
	Wall to Wall	11000	11000	11200	11200	13000	13800
Load Rating	Front Axle	2180	2180	2360	2360	2570	3100
	Rear Axle	4120	4120	4400	4400	4860	6000
Wheel Base	2525	2525	2810	2810	3430	3430	3430
Overall length	4760	4760	5105	5105	5860	5860	5880
Width	1880	1880	2030	2030	2130	2130	2130
Height	2100	2100	2200	2200	2230	2230	2260
Fuel Tank Capacity	80 lts	80 lts	100 lts	100 lts	170 lts	170 lts	170 lts

PERFORMANCE DATA

Max Theoretical Speed	120 km/h	130 km/h	140 km/h	131 km/h	142 km/h	131 km/h	119 km/h
Engine speed @ 100 km/h	2600 rpm	2250 rpm	2250 rpm	2400 rpm	2200 rpm	2400 rpm	2600 rpm
Wheels & Tyres	185/85 R16	185/85 R16	195/85 R16	195/85 R16	205/85R 16	205/85R 16	225/80R 17.5
Final Drive Ratio	4.625 : 1	4.625 : 1	4.625 : 1	4.1:1	4.875 : 1	4.3: 1	4.875 : 1
Approx Mass - kg	Total	2690	2740	3050	3030	3435	3460
	Front	1448	1478	1699	1699	1801	1826
	Rear	1242	1262	1351	1331	1629	1619
	GVM STD	4495	4495	4495	4495	6500	6500
	OPT	5500	5500	5500	5500	4495	4495
	GCM STD	7995	7300	7300	7995	7300	10000
OPT	9000	7300	7300	9000	7300	7995	

Approximate mass includes standard tools, 10 litres of fuel, spare tyre and is subject to a +/- 3% variance

WARRANTY

New vehicle warranty period

Light Duty Model	Axle configuration	Standard warranty (whichever comes first)	Cab corrosion perforation
300 SERIES Tipper Range	4 x 2	3 years or 100,000km	36 months

Battery warranty – 12 months from date of delivery

Genuine parts or accessories warranty – 3 years unlimited kilometres when fitted by an authorised Hino dealer *

* For conditions, refer to the Hino Parts & Service warranty brochure



DISCLAIMER

Important notice. Hino Trucks are distributed in Australia by Hino Motor Sales Australia Pty Ltd A.C.N. 064 989 724.

All efforts have been made to ensure the information contained in this brochure was correct at time of printing or uploading. Hino Motor Sales Australia Pty Ltd reserves the right to alter any details of the specifications & equipment without notice. Hino in so far as it is permitted by law to do so, shall not be liable in any way as a result of any reliance placed by any person on anything contained in this brochure. You should therefore check with your authorised Hino dealer at the time of ordering your motor vehicle to ensure that colour, specifications, equipment, design features & options are available for the vehicle you are ordering. Please note that some options may only be available in combination with others. Authorised Hino dealers will on request provide up to date information on all accessories, design features, prices & availability.

HS300TIPPER-0615