

HINO

300 Series

Tipper Range



*Image may contain items not standard to the model

KEY FEATURES

Factory Tipper bodies with drop sides
 STD Cab, Wide & Crew Cab variants
 Pre-Collision System (PCS) including AEB & PD
 Vehicle Stability Control (VSC) including ABS & TC
 Lane Departure Warning System (LDWS)
 Daytime Running Lamps (DRL)
 Dual SRS Airbags
 Reverse Camera
 ECE R-29 Cab Strength Certified
 Cruise Control
 ADR 80/03 Emission level using Euro 5 Standard

KEY SPECIFICATIONS

GVM. 4,495 to 8,500 kg
GCM. GVM + 3,500kg
 Automatic up to 8,000kg
Power range 150hp to 165hp
Torque range 420Nm to 464Nm
Transmissions. . STD cab . . 5 spd Manual & 6 spd Automatic
 Wide cab . . 6 spd Manual & 6 spd Automatic
Wheelbases.2.5m to 4.2m*
Internal body length3.0m to 4.0m*

*See Model details for exact dimensions

MODEL DETAILS



Model Description			616 AT 2525 STD TIP PRO		616 AT 2525 STD TIPPER		616 MT 2525 STD TIPPER		616 AT 2810 WIDE TIP PRO		616 AT 2810 WIDE TIPPER		617 MT 2810 WIDE TIPPER		716 AT 3430 WIDE TIP PRO		717 MT 3430 WIDE TIPPER		717 MT 3430 WIDE TIP PRO		917 MT 3430 WIDE TIP PRO		717 MT 4200 WIDE CREW TIP PRO		816 AT 4200 WIDE CREW TIP PRO		917 MT 4200 WIDE CREW TIP PRO					
Product Code			XZU605R-WKTMSQ3 TP		XZU605R-WKTMSQ3 T		XZU605R-WKMMSQ3 T		XZU700R-WKTMSQ3 TP		XZU700R-WKTMSQ3 T		XZU700R-WKFMTQ3 T		XZU710R-WKTQSQ3 TP		XZU710R-WKFQTQ3 T		XZU710R-WKFQTQ3 TP		XZU710R-WKFTTQ3 TP		XZU730R-ZKFQTQ3 TP		XZU730R-ZKTSSQ3 TP		XZU730R-ZKFTTQ3 TP					
TIPPER BODY																																
Cubic Capacity			1.9m³					2.1m³					3.0m³					3.2m³					3.4m³									
Internal length (mm)			3,000					3,100					3,600					3,800					4,000									
Internal width (mm)			1,750					1,900					2,000					2,000														
Drop sides & tailgate height (mm)			370					370					430					430														
Deck plate thickness (mm)			3.2					3.2					3.2					4.5					3.2					4.5				
Front plate thickness (mm)			3.2					3.2					2.3					3.2					2.3					3.2				
Drop sides thickness (mm)			2.3					2.3					2.3					3.2					3.2					3.2				
Tailgate thickness (mm)			3.2		2.3			3.2		2.3			3.2		2.3			3.2			3.2					3.2						
Tipping angle (deg)			60°					60°					55°					50°														
Hydraulic cylinder bore & stroke (mm)			100 x 350					100 x 350					100 x 480					100 x 510														
Hydraulic pump model			VC02-04			VC02-03		VC02-06					VC03-15					VC03-15														
Control			Lever in the cab					Lever in the cab					Lever in the cab					Lever in the cab														
Body Lock			Equipped		N/A			Equipped		N/A			Equipped		N/A			Equipped			Equipped											
Rear Gate type			Barn door		Single Gate			Barn door		Single Gate			Barn door		Single Gate			Barn door			Barn door											
Swinging gates to allow clear access to deck			Equipped		N/A			Equipped		N/A			Equipped		N/A			Equipped			Equipped											
Tailgate operation with tipper control			Auto release from bottom					Auto release from bottom					Auto release from bottom					Auto release from bottom														
VEHICLE DETAILS																																
Engine speed @ 100 Km/h			2,230rpm			2,500rpm		2165rpm			2,128rpm		2,246rpm		2213rpm			2,458rpm		2,213rpm		2,525rpm		2,458rpm								
Max theoretical speed			139km/h			124km/h		143km/h			145km/h		138km/h		140km/h			126km/h		140km/h		122km/h		126km/h								
Engine Power & Torque (hp & Nm)			150hp / 420Nm					150hp / 420Nm					165hp / 464Nm		150hp / 420Nm			165hp / 464Nm					165hp / 464Nm		150hp / 420Nm		165hp / 464Nm					
Transmission type & number of forward gears			Automatic 6 speed			Manual 5 speed		Automatic 6 speed			Manual 6 speed		Automatic 6 speed		Manual 6 speed					Manual 6 speed		Automatic 6 speed		Manual 6 speed								
Fuel Tank Capacity			80 L					100 L					150 L					100 L														
Wheels & Tyres			185/85R16					195/85R16					215/85R16					225/80R17.5		215/85/R16		225/80R17.5										
Seating capacity			3					3					3					7														
DIMENSIONS – (mm)/WEIGHTS – (kg)																																
Wheelbase (WB)			2,525					2,810					3,430					4,200														
Overall length (OL)			4,760					5,115					5,870					6,975					7,025									
Overall width (OW)			1,880					1,995					2,130					2,190														
Cab width			1,695					1,995					1,995					1,995														
Overall height (OH)			2,100					2,190					2,230					2,230		2,250		2,260										
Front Overhang (FOH)			980					1,115					1,115					1,115														
Road Clearance (RC)			170					170					185					200		180		200										
Front Track (FT)			1,400					1,665					1,665					1,665														
Rear Track (RT)			1,435					1,480					1,520					1,590		1,520		1,590										
Turning circle		Kerb to Kerb	9,600					9,800					11,400					12,400		13,800		14,800										
		Wall to Wall	10,800					11,200					12,800					13,800		15,200		16,200										
Indicative chassis mass–kg (STD tools, 10 litres of fuel, spare tyre & subject to a +/- 3% tolerance)																																
Total			2,835		2,795		2,755		3,140		3,100		3,070		3,595		3,520		3,560		3,745		3,815		3,915		4,030					
Front			1,495		1,520		1,495		1,740		1,765		1,745		1,890		1,890		1,865		1,880		1,995		2,020		1,980					
Rear			1,340		1,275		1,260		1,400		1,335		1,325		1,705		1,630		1,695		1,865		1,820		1,895		2,050					
Standard Ratings		GVM	4,495kg					4,495kg					6,500kg					7,995kg		6,500kg		8,000		7,995								
		GCM	7,995kg					7,995kg					8,000kg		10,000kg			11,495kg		10,000kg		8,000		11,495								
Optional Ratings		GVM	5,500kg					5,500kg					4,495kg					8,500kg		4,495kg		4,495		8,500								
		GCM	8,000kg			9,000kg		8,000kg			9,000kg		7,995kg					12,000kg		7,995kg		7,995		12,000								

SAFETY FEATURES

Active Safety Features			
Vehicle Stability Control	VSC	Equipped	
Anti-lock Brake System	ABS	Equipped	
Pre-Collision System	PCS	Equipped	
PCS is inclusive of	Autonomous Emergency Braking		AEB
	Pedestrian Detection		PD
	Lane Departure Warning System		LDWS
Traction Control	TC	Equipped	
Reverse Camera	RC	Equipped	
ES Start (MT models only)	ES	Equipped	
Daytime Running Lamps	DRL	Equipped	
Reverse Buzzer		Equipped	
Passive Safety Features			
ECE-R29 Cab Strength Certification		Equipped	
SRS airbags for driver & side passenger		Equipped	
SRS seatbelt pretensioner for driver & side passenger		Equipped	
Shock absorbing & collapsible steering column		Equipped	
Door Impact Beams		Equipped	

TIPPER BODY FEATURES

All steel construction with underbody hoist
Auto release tail gate
Drop sides & tail gate
Body lock, rope rails & barn door (TIP PRO models)

GENUINE ACCESSORY OPTIONS

Bullbar or Nudge bar
Chrome wheel covers
Cameras (up to additional 3 extra)
Dash Camera (DVR Camera System)
Dash mat
Floor mats
GPS navigation with live traffic (Truck spec)
Retracting Tarp
Seat covers (Wool, Canvas, Carbon)
Stone guard
Sunvisor
Weathershields
Please check with your dealer for availability, price & fitment

For Cab Chassis related specifications not included in this document please refer to the applicable Cab Chassis spec sheet or Body mounting Manual

WARRANTY

New vehicle warranty period

Light Duty Model	Axle configuration	Standard warranty (whichever comes first)	Cab corrosion perforation
300 Series	4 x 2	5 years or 250,000km	60 months

Battery warranty – 12 months from date of delivery

* For conditions, refer to the Hino Parts & Service warranty brochure

Genuine parts or accessories warranty – 3 years unlimited kilometres when fitted by an authorised Hino dealer *

Built to Go Body warranty – 5 years or 250,000km (whichever comes first)



DISCLAIMER

Important notice – Hino Trucks are distributed in Australia by Hino Motor Sales Australia Pty Ltd A C N 064 989 724. All efforts have been made to ensure the information contained in this brochure was correct at time of printing or uploading. Hino Motor Sales Australia Pty Ltd reserves the right to alter any details of the specifications and equipment without notice. Hino in so far as it is permitted by law to do so, shall not be liable in any way as a result of any reliance placed by any person on anything contained in this brochure. You should therefore check with your authorised Hino dealer at the time of ordering your motor vehicle to ensure that colour, specifications, equipment, design features and options are available for the vehicle you are ordering. Please note that some options may only be available in combination with others. Authorised Hino dealers will on request provide up to date information on all accessories, design features, prices & availability.