

HINO

300 Series

Tipper Range



*Image may contain items not standard to the model

KEY FEATURES

- Factory Tipper bodies with drop sides
- STD Cab & Wide Cab variants
- Pre-Collision System (PCS) including AEB & PD
- Vehicle Stability Control (VSC) including ABS & TC
- Lane Departure Warning System (LDWS)
- Daytime Running Lamps (DRL)
- Dual SRS Airbags
- Reverse Camera
- ECE R-29 Cab Strength Certified
- Cruise Control**
- ADR 80/03 Emission level using Euro 5 Standard



KEY SPECIFICATIONS

GVM.	4,495 to 6,500 kg
GCM.	GVM + 3,500kg
	Automatic up to 8,000kg
Power range	150hp to 165hp
Torque range	420Nm to 464Nm
Transmissions.	STD cab . . . 5 spd Manual & 6 spd Automatic
	Wide cab . . . 6 spd Manual & 6 spd Automatic
Wheelbases.	.2.5m to 4.2m*
Internal body length	.3.0m to 3.6m*

*See Model details for exact dimensions

MODEL DETAILS




Model Description	616 AT 2525 STD TIPPER		616 MT 2525 STD TIPPER
Product Code	XZU605R-WKTMSQ3 T		XZU605R-WKMMSQ3 T
TIPPER BODY			
Cubic Capacity			1.9m ³
Internal length (mm)			3,000
Internal width (mm)			1,750
Drop sides & tailgate height (mm)			370
Deck plate thickness (mm)			3.2
Front plate thickness (mm)			3.2
Drop sides thickness (mm)			2.3
Tailgate thickness (mm)			3.2
Tipping angle (deg)			60°
Hydraulic cylinder bore & stroke (mm)			100 x 350
Hydraulic pump model	VC02-04		VC02-03
Control	Lever in the cab		
Rope hooks	Equipped		
Rear Gate type	Single gate hinged from the top		
Shovel holder	Equipped		
Tailgate operation with tipper control	Auto release from bottom		
VEHICLE DETAILS			
Engine speed @ 100 Km/h	2,230rpm		2,500rpm
Max theoretical speed	139km/h		124km/h
Engine Power & Torque (hp & Nm)			150hp / 420Nm
Transmission type & number of forward gears	Automatic 6 speed		Manual 5 speed
Fuel Tank Capacity			80 L
Wheels & Tyres			185/85R16
Seating capacity			3
DIMENSIONS – (mm)/WEIGHTS – (kg)			
Wheelbase (WB)			2,525
Overall length (OL)			4,760
Overall width (OW)			1,880
Cab width			1,695
Overall height (OH)			2,100
Front Overhang (FOH)			980
Road Clearance (RC)			170
Front Track (FT)			1,400
Rear Track (RT)			1,435
Turning circle	Kerb to Kerb	9,600	
	Wall to Wall	10,800	
Indicative chassis mass – kg (STD tools, 10 litres of fuel, spare tyre & subject to a +/- 3% tolerance)			
Total	2,795		2,755
Front	1,520		1,495
Rear	1,275		1,260
Standard Ratings	GVM	4,495kg	
	GCM	7,995kg	
Optional Ratings	GVM	5,500kg	
	GCM	8,000kg	



Drawings are for reference only to the dimensions table above.

MODEL DETAILS

Model Description	616 AT 2810 WIDE TIPPER	617 MT 2810 WIDE TIPPER	717 MT WIDE TIPPER
Product Code	XZU700R-WKTMSQ3 T	XZU700R-WKFMTQ3 T	XZU710R-WKFQTQ3 T
TIPPER BODY			
Cubic Capacity	2.1m ³		3.0m ³
Internal length (mm)	3,100		3,600
Internal width (mm)	1,900		2,000
Drop sides & tailgate height (mm)	370		430
Deck plate thickness (mm)		3.2	
Front plate thickness (mm)	3.2		2.3
Drop sides thickness (mm)		2.3	
Tailgate thickness (mm)		2.3	
Tipping angle (deg)	60°		55°
Hydraulic cylinder bore & stroke (mm)	100 x 350		100 x 480
Hydraulic pump model	VC02-06		VC03-15
Control	Lever in the cab		
Rope hooks	Equipped		
Rear Gate type	Single gate hinged from the top		
Shovel holder	Equipped		
Tailgate operation with tipper control	Auto release from bottom		
VEHICLE DETAILS			
Engine speed @ 100 Km/h	2165rpm	2,128rpm	2213rpm
Max theoretical speed	143km/h	145km/h	140km/h
Engine Power & Torque (hp & Nm)	150hp / 420Nm	165hp / 464Nm	
Transmission type & number of forward gears	Automatic 6 speed	Manual 6 speed	
Fuel Tank Capacity	100 L		150 L
Wheels & Tyres	195/85R16		215/85R16
Seating capacity	3		
DIMENSIONS – (mm)/WEIGHTS – (kg)			
Wheelbase (WB)	2,810		3,430
Overall length (OL)	5,115		5,870
Overall width (OW)	1,995		2,130
Cab width		1,995	
Overall height (OH)	2,190		2,230
Front Overhang (FOH)		1,115	
Road Clearance (RC)	170		185
Front Track (FT)		1,665	
Rear Track (RT)	1,480		1,520
Turning circle	Kerb to Kerb	9,800	11,400
	Wall to Wall	11,200	12,800
Indicative chassis mass – kg (STD tools, 10 litres of fuel, spare tyre & subject to a +/- 3% tolerance)			
Total	3,100	3,070	3,560
Front	1,765	1,745	1,865
Rear	1,335	1,325	1,695
Standard Ratings	GVM	4,495kg	6,500kg
	GCM	7,995kg	10,000kg
Optional Ratings	GVM	5,500kg	4,495kg
	GCM	8,000kg	9,000kg



For specific layouts please refer to the applicable body mounting manual. (BMM)

SAFETY FEATURES

Active Safety Features		
Vehicle Stability Control	VSC	Equipped
Anti-lock Brake System	ABS	Equipped
Pre-Collision System	PCS	Equipped
PCS is inclusive of	Autonomous Emergency Braking	AEB
	Pedestrian Detection	PD
	Lane Departure Warning System	LDWS
Traction Control	TC	Equipped
Reverse Camera	RC	Equipped
ES Start (MT models only)	ES	Equipped
Daytime Running Lamps	DRL	Equipped
Reverse Buzzer		Equipped
Passive Safety Features		
ECE-R29 Cab Strength Certification		Equipped
SRS airbags for driver & side passenger		Equipped
SRS seatbelt pretensioner for driver & side passenger		Equipped
Shock absorbing & collapsible steering column		Equipped
Door Impact Beams		Equipped

TIPPER BODY FEATURES

All steel construction with underbody hoist
Auto release tail gate
Drop sides & tail gate

GENUINE ACCESSORY OPTIONS

Bullbar or Nudge bar
Chrome wheel covers
Cameras (up to additional 5 extra)
Dash Camera (DVR Camera System)
Dash mat
Floor mats
GPS navigation with live traffic (Truck spec)
Retracting Tarp
Seat covers (Wool, Canvas, Carbon)
Stone guard
Sunvisor
Weathershields
UHF CB Radio Kit
Please check with your dealer for availability, price & fitment

For Cab Chassis related specifications not included in this document please refer to the applicable Cab Chassis spec sheet or Body mounting Manual

WARRANTY


New vehicle warranty period

Light Duty Model	Axle configuration	Standard warranty (whichever comes first)	Cab corrosion perforation
300 Series	4 x 2	5 years or 250,000km	60 months

Battery warranty – 12 months from date of delivery

Genuine parts or accessories warranty – 3 years unlimited kilometres when fitted by an authorised Hino dealer *

* For conditions, refer to the Hino Parts & Service warranty brochure



DISCLAIMER

Important notice – Hino Trucks are distributed in Australia by Hino Motor Sales Australia Pty Ltd A C N 064 989 724. All efforts have been made to ensure the information contained in this brochure was correct at time of printing or uploading. Hino Motor Sales Australia Pty Ltd reserves the right to alter any details of the specifications and equipment without notice. Hino in so far as it is permitted by law to do so, shall not be liable in any way as a result of any reliance placed by any person on anything contained in this brochure. You should therefore check with your authorised Hino dealer at the time of ordering your motor vehicle to ensure that colour, specifications, equipment, design features and options are available for the vehicle you are ordering. Please note that some options may only be available in combination with others. Authorised Hino dealers will on request provide up to date information on all accessories, design features, prices & availability. **Maximum Cruise control setting 106 km/h.